



US 20200282295A1

(19) **United States**(12) **Patent Application Publication****Chen et al.**(10) **Pub. No.: US 2020/0282295 A1**(43) **Pub. Date: Sep. 10, 2020**(54) **AUTO-BALANCING DEVICE WITH
LONGITUDINALLY DISPOSED AND
MOVABLE PLATFORM SECTIONS***A63C 17/01* (2006.01)*B62J 45/415* (2006.01)(52) **U.S. Cl.**CPC *A63C 17/12* (2013.01); *B62K 11/007*
(2016.11); *A63C 17/014* (2013.01); *B62J*
45/4151 (2020.02); *B60L 2260/34* (2013.01);
A63C 2203/12 (2013.01); *A63C 2203/18*
(2013.01); *B60L 2240/22* (2013.01); *B60L*
2200/16 (2013.01)(71) Applicants: **Shane Chen**, Camas, WA (US);
Ywanne Chen, Camas, WA (US)(72) Inventors: **Shane Chen**, Camas, WA (US);
Ywanne Chen, Camas, WA (US)(21) Appl. No.: **16/739,085**(22) Filed: **Jan. 9, 2020****Related U.S. Application Data**(60) Provisional application No. 62/790,301, filed on Jan.
9, 2019.**Publication Classification**(51) **Int. Cl.***A63C 17/12* (2006.01)*B62K 11/00* (2006.01)

(57)

ABSTRACT

An auto-balancing transportation device configured for being ridden in a foot forward or sideways standing position. The rider platform has front and rear foot platform areas and two connecting members, located on opposite lateral sides of the device, that couple the front and rear platform areas. Two drive wheels are located under or through the platform. The front and/or rear platform areas are movable or twistable so as to alter the fore-aft tilt of one or more of the connecting members. Position sensors associated with each connecting member are used to drive a corresponding drive wheel. In this manner, differences in fore-aft tilt angle of the two connecting members achieves a turning of the device.

